



Gömme Yer Armatürleri | In-Ground luminaires



LED TİPİ LED TYPE	Renk ısısı Color Temperature	Toplam Güç Total Power	Akim Current	Volaj Voltage	Toplam Lümen Total Lumen
Power Led	3000K	15W	500mA	220V AC	1422lm
Power Led	4000K	15W	500mA	220V AC	1587lm
Power Led	6500K	15W	500mA	220V AC	1788lm

Malzeme: Alüminyum enjeksiyon gövde ısıya dayanıklı 15mm cam ve termoplastik ankastre montaj kasası

Renk : Füme Metalik Gri Siyah

Armatürün yüzeyine elektrostatik toz boyadan önce korozyon direncini artırıcı zincrim uygulanır. Led sürücüsü dahil


Material : Die-cast aluminium body toughened glass with 15mm and thermoplastic recessed box

Color : Graphite Metallic Grey Black

For corrosion resistance, zincrim applied to surface of the luminaire before electrostatic powder coating . With Led driver

514L11

Power Led



9MNK26

Ankastre Montaj Kasası / Recessed Box



IP67



518111



MAX.20W.-35W. HIT-TC-CE G8.5

510107



MAX.75W. QPAR30 E27



Hareketli Yük Dayanımı : 2000 kg - 20 km/h
Moving Load Resistance : 2000 kg - 20 km/h

<https://stilas.com.tr/urun/514l11-9mnk26/>

 **STİLAS**