



Gömme Yer Armatürleri | In-Ground luminaires



LED TİPİ LED TYPE	Renk Isısı Color Temperature	Toplam Güç Total Power	Akim Current	Volaj Voltage	Toplam Lümen Total Lumen
Power Led	3000K	15W	500mA	220V AC	1422lm
Power Led	4000K	15W	500mA	220V AC	1587lm
Power Led	6500K	15W	500mA	220V AC	1788lm

Malzeme: Alüminyum enjeksiyon gövde ve paslanmaz çelik ön kapak ısıya ve basınca dayanıklı 15mm cam ve termoplastik akastre montaj kasası

Renk : Mat Çelik

Armatürün yüzeyine elektrostatik toz boyadan önce korozyon direncini artırıcı zincrim uygulanır. Led sürücüsü dahil


Material : Die-cast aluminium body and stainless-steel front frame toughened glass with 15mm and termoplastic recessed box

Color : Mat Steel

For corrosion resistance, zincrim applied to surface of the luminaire before electrostatic powder coating . With Led driver

514L12

Power Led



9MNK26

Ankastre Montaj Kasası / Recessed Box



IP67



518112



MAX.20W.-35W. HIT-TC-CE G8.5

510108



MAX.75W. QPAR30 E27



Hareketli Yük Dayanımı : 2000 kg - 20 km/h
Moving Load Resistance : 2000 kg - 20 km/h

<https://stilas.com.tr/urun/514l12-9mnk26/>

STİLAS