



Gömme Yer Armatürleri | In-Ground luminaires



LED TİPİ LED TYPE	Renk ısısı Color Temperature	Toplam Güç Total Power	Akim Current	Volaj Voltage	Toplam Lümen Total Lumen
Power Led	3000K	15W	500mA	220V AC	1422lm
Power Led	4000K	15W	500mA	220V AC	1587lm
Power Led	6500K	15W	500mA	220V AC	1788lm

Malzeme: Alüminyum enjeksiyon gövde ısıya ve basınca dayanıklı 15mm cam ve termoplastik akastre montaj kasası

Renk : Mat Çelik

Armatürün yüzeyine elektrostatik toz boyadan önce korozyon direncini artırıcı zincrim uygulanır. Led sürücüsü dahil


Material : Die-cast aluminium body toughened glass with 15mm and thermoplastic recessed box

Color : Mat Steel

For corrosion resistance, zincrim applied to surface of the luminaire before electrostatic powder coating . With Led driver

514L13	195x195 210 160 155	9MNK26 Akastre Montaj Kasası / Recessed Box	IP67			
Power Led						

518112	510108
MAX.20W. -35W. HIT-TC-CE G8.5	MAX.75W. QPAR30 E27



Hareketli Yük Dayanımı : 2000 kg - 20 km/h
Moving Load Resistance : 2000 kg - 20 km/h

<https://stilas.com.tr/urun/514l13-9mnk26/>

