



Gömme Yer Armatürleri | In-Ground luminaires



LED TİPİ LED TYPE	Renk Isısı Color Temperature	Toplam Güç Total Power	Akim Current	Volaj Voltage	Toplam Lümen Total Lumen
Power Led	3000K	34W	700mA	220V AC	2880lm
Power Led	4000K	34W	700mA	220V AC	3648lm
Power Led	6500K	34W	700mA	220V AC	3960lm

Malzeme: Alüminyum enjeksiyon gövde ve paslanmaz çelik ön kapak ısıya ve basınca dayanıklı 15mm cam ve termoplastik ankastre montaj kasası

Renk : Mat Çelik

Armatürün yüzeyine elektrostatik toz boyadan önce korozyon direncini artırıcı zincoprim uygulanır. Led sürücüsü dahil


Material : Die-cast aluminium body and stainless-steel front frame
toughened glass with and thermoplastic recessed box

Color : Mat Steel

For corrosion resistance, zincoprim applied to surface of the luminaire before electrostatic powder coating . With Led driver

514L15

Middle Power Led



9MNK27

Ankastre Montaj Kasası / Recessed Box



IP67



518106



MAX.20W.-35W. HIT-TC-CE G8.5



Hareketli Yük Dayanımı : 2000 kg - 20 km/h
Moving Load Resistance : 2000 kg - 20 km/h

<https://stilas.com.tr/urun/514l15-9mnk27/>

 **STILAS**